

**LAN TEK**

# AutoView 1500 KVM Switch



The AutoView® 1500 KVM switching system includes multi-platform support, advanced cabling options and a convenient on-screen display

## Features and Benefits

Avocent® AutoView 1500 8-port, dual user KVM switch provides PS/2, USB, Sun and serial connections, advanced cabling options, flexible access and a next-generation user interface in one switching solution.

The AutoView 1500 switch server interface modules and integrated access cables automatically assign and retain unique server names, which simplifies installation and eases re-configuration. With advanced on-screen management and flexible access for two simultaneous users, the AutoView 1500 switching system is the ideal solution for today's small office and mid-sized business networking environments.

- Integrated access cables offer PS/2 or USB keyboard, video and mouse connectivity in one, slim CAT 5 cable. No cable bulk, saves time and reduces cost.
- Server interface modules support all major server platforms and VT100 serial-based devices.
- Provides two simultaneous local users with access to eight PCs and network devices.
- Advanced on-screen management provides easy configuration and server selection.
- BIOS-level access ensures connection to the attached servers regardless of the health or type of operating system.
- A space-saving 1U rack mount design.
- Flash-upgrades firmware for fast and easy updates for appliances and server interface modules.
- Keep Alive power safeguard allows attached servers to continue network functions in the event of power failure to the switch.
- Includes rack mount kit.

<b>Mechanical</b>	Height	1.75 in. (4.45 cm)
	Width	17.00 in. (43.18 cm)
	Depth	11.00 in. (27.94 cm)
	Weight	8 lbs. (3.6 kg)
<b>Environmental</b>	Operating Temp	50 to 122 F (10 to 50 C)
	Storage Temp	-4 to 140 F (-20 to 60 C)
<b>Power</b>	Operating Voltage	100 - 240 VAC Autosensing
	Power	50/60 Hz
	Frequency	
	Input	40 W Maximum
<b>Supported Hardware</b>	Computers	IBM PC/AT, PC and 100% compatibles
	Monitors	XGA, XGA-II with adapter, 1600 x 1280 @ 75 Hz resolution

	Peripherals	PC keyboard, PC mouse, Microsoft Explorer mouse, Microsoft IntelliMouse family, IBM Scrollpoint, Logitech Mouseman Wheel, Logitech Trackman Marble Wheel, Logitech Marble FX and Kensington 4-button mouse
<b>Standards</b>	Approved Agency	UL FCC Class A, cUL, ICES Class A, CE, N, GS, IRAM, GOST, VCCI, Class A, MIC Class A, C-Tick

**LAN TEK**  
**800.660.2286**

Fax: 760.364.4997

Email: [lantek@earthlink.net](mailto:lantek@earthlink.net)

Web: [www.LAN-TEK.NET](http://www.LAN-TEK.NET)

P. O. Box 549  
Yucca Valley, CA 92286