

10.4" LCD RACK MOUNT MONITOR WITH 24W SPEAKERS



- 10.4" TFT LCD display (1024 x 768 resolution) in only 5U (8.75") of rack space.
- ARGB (Analog RGB) and DVI-D signal inputs (optional S-Video/Composite Video inputs).
- Housed in rugged steel construction with a black powder coat finish.
- Integrated 24 Watt stereo speaker with front panel controls.
- Optional Lexan™ screen protection available (L).

GENERAL SPECIFICATIONS

Dimensions:

19.0" (W) x 8.75" (H) x 5.0" (D).

Weight:

10 lbs

Power:

110 - 240 VAC, 50/60 Hz.
60 Watts max.

On-Screen Controls:

Brightness, Contrast, Horizontal & Vertical
Position, Auto Adjust, OSD H & V Position, Input Select
Color Temp., Reset.

Plug & Play:

DDC1 and DDC2B

Temperature:

Operating: 0°C to 50°C
Storage: -20°C to 60°C

Humidity:

Operating: 10 to 90% RH (max)

Input Signal (VGA):

R.G.B. analog video, TTL H & V sync.

Input Signal (Digital):

DVI-D (TDMS).

Input Connectors:

Analog: 15 pin mini D-Sub.
Digital: 24 pin DVI-D.

Colors Available:

Black.

Specifications subject to change without notice.

DISPLAY SPECIFICATIONS

Display Type:

Active matrix TFT LCD

Display area:

10.4" Diagonal.

Colors Displayed:

262K colors.

Contrast Ratio:

500:1 typ.

Brightness:

350 cd/m² typ.

Viewing Angle:

Horizontal: 178°

Vertical: 178°

SPEAKER SPECIFICATIONS

Front Panel Controls:

Power ON/OFF switch, Volume control,
Headphone Jack, Power Indicator.

Audio Output:

24 Watts.

Audio Input Connector:

3.5mm stereo jack.

MODEL NUMBER

LTRM-101S(X)(X)

- Blank = No S-Video/Composite Input.
- V = S-Video/Composite Video input.
- Blank = No Screen Protection.
- L = Lexan™ Screen Protection.

Contact us about additional rack mount products.



Tel: 760-364-2900
Web: www.lan-tek.net, www.lantekrackmount.com
P. O. Box 549

LAN TEK
1-800-660-2286

Fax: 760-364-4997
email: lantek@earthlink.net
Yucca Valley, CA 92286