

# 20.1" LCD RACK MOUNT MONITOR



- 20.1" TFT LCD display with 1600 x 1200 resolution.
- Steel construction with a durable powder coat finish.
- High contrast ratio for excellent picture quality.
- Optional Lexan™ screen protection.
- Mounts in 8U of rack space.
- Analog and Digital inputs.

## GENERAL SPECIFICATIONS

### Dimensions:

19.0" (W) x 14.0" (H) x 3.4" (D)

### Weight:

18.0 lbs.

### Power:

90 ~ 265 VAC, 50/60 Hz (47.5~63 Hz).  
55 Watts typ.

### On-Screen Controls:

Brightness, Contrast, Positioning, Color temperature,  
Individual color control, Image control, Input selection, clock,  
clock phase, Reset.

### Plug & Play:

DDC1 and DDC2B

### Temperature:

Operating: 5°C to 35°C  
Storage: -10°C to 60°C

### Humidity:

Operating: 20 to 80% RH (max)

### Input Signal:

Two DVI-I connectors (dual VGA analog or dual digital  
input possible).

### Sync Input:

Separate sync (HSYNC/VSYNC),  
composite sync, sync on green.

### Video Cables:

Two VGA to DVI-I, two DVI-D to DVI-I.

### Colors Available:

Black.

## DISPLAY SPECIFICATIONS

### Display Type:

Active matrix TFT LCD

### Display area:

20" Diagonal.

### Colors Displayed:

16.8 million colors.

### Contrast Ratio:

800:1

### Brightness:

300 cd/m<sup>2</sup> typ.

### Viewing Angle (CR>10):

Horizontal: 178°

Vertical: 178°

### Response Time:

8 ms (G-G).

### Resolution:

VGA up to 1600 x 1200.

### Horizontal Frequency:

30 to 94 KHz.

### Vertical Frequency:

48 to 85 Hz.

Specifications subject to change without notice.

## MODEL NUMBER

LTRM-420L(X)

- Blank = No screen protection installed.
- L = With Lexan™ screen protection installed.

Contact us about other options and our additional rack mount products.



www.lan-tek.net

Tel: 760-364-2900

Fax: 760-364-4997

**LAN TEK**  
**1-800-660-2286**

lantek@earthlink.net

P. O. Box 549

Yucca Valley CA 92286